

Summary

- > Single output: power 30W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

129×98×38mm

Specification	Model	D-30A		D-30B		D-30C		D-30F	
		CH1	CH2	CH1	CH2	CH1	CH2	CH1	CH2
DC output voltage, current		5V 0~4A	12V 0~1A	5V 0~2A	24V 0~0.1A	12V 0.5~1.5A	-12V 0.2~1A	12V 0.3~1A	24V 0.3~1A
Wave and noise		50mVp-p	100mVp-p	50mVp-p	100mVp-p	100mVp-p	100mVp-p	100mVp-p	120mVp-p
Inlet wire stability		±0.5%	±1%	±0.5%	±1%	±0.5%	±1%	±0.5%	±1%
Load stability		±0.5%	±4%	±0.5%	±4%	±0.5%	±4%	±0.5%	±4%
Efficiency		72%		74%		74%		75%	
Adjustable range for DC voltage		CH1: ±10%	CH2: ±5%	CH1: ±10%	CH2: ±5%	CH1: ±10%	CH2: ±5%	CH1: ±10%	CH2: ±5%
Input voltage range		90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz							
Impact current		Cold start current 18A/115VAC 36A/230VAC							
Overload protection		105%~150% cut off the output, automatic recovery							
Other protection		Over current protection / Short-circuit protection							
Setup, rise, hold up time		200ms, 50ms, 30ms/230VAC at full load							
Withstand voltage		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute							
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ							
Working temperature		-10℃~+50℃							
Dimension		129×98×38mm							
Weight		0.4kg							
Packing		43×32.5×24CM/45PCS/18kg							

Overall dimension(mm)

