

Summary

- > Single output: power 60W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

159×98×38mm

Specification	Model	D-60A		D-60B		D-60C		D-60F	
		CH1	CH2	CH1	CH2	CH1	CH2	CH1	CH2
DC output voltage, current		5V 0~4A	12V 0~3A	5V 0~3A	24V 0~1.8A	12V 1~2.5A	-12V 0.3~2.5A	12V 1~2A	24V 0.2~1.5A
Wave and noise		70mVp-p	150mVp-p	75mVp-p	150mVp-p	100mVp-p	100mVp-p	100mVp-p	120mVp-p
Inlet wire stability		±0.5%	±1%	±0.5%	±0.5%	±1%	±1%	±1%	±1%
Load stability		±0.5%	±4%	±0.5%	±4%	±5%	±5%	±0.5%	±8%
Efficiency		73%		76%		73%		73%	
Adjustable range for DC voltage		CH1: ±10%	CH2: ±5%	CH1: ±10%	CH2: ±5%	CH1: ±10%	CH2: ±10%	CH1: ±10%	CH2: ±10%
Input voltage range		85~264VAC 120~370VDC 47~63Hz							
Impact current		Cold start current 30A/115VAC 60A/230VAC							
Overload protection		105%~150% cut off the output, automatic recovery							
Over voltage protection		CH1:115%~135% shut down O/P voltage, re-power on to recover							
Setup, rise, hold up time		300ms, 50ms, 80ms/230VAC at full load							
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute							
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ							
Working temperature		-10℃~+50℃							
Dimension		159×98×38mm							
Weight		0.55kg							
Packing		34×32×24CM/30PCS/16.5kg							

Overall dimension(mm)

