

Summary

> Single output power: 75W

> Input voltage: 85~264VAC 120~370VDC



General Specification

55.5x125.2x100mm

Specification	Model	DR-75-12	DR-75-15	DR-75-24	DR-75-48
DC output voltage, current		12V 0~6.3A	15V 0~5A	24V 0~3.2A	48V 0~1.6A
Wave and noise		100mVp-p	150mVp-p	150mVp-p	240mVp-p
Inlet wire stability		±0.5 %	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		76%	80%	80%	81%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	85~264VAC 120~370VDC 47~63Hz				
Impact current	Cold start current 20A/115VAC 40A/230VAC				
Overload protection	105%~150% cut off the output, automatic recovery				
Over voltage protection	121%~142% shut down O/P voltage, re-power on to recover				
Setup, rise, hold up time	1000ms, 60ms, 60ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ				
Working temperature	-10℃~+50℃				
Dimension	55.5×125.2×100mm				
Weight	0.55kg				
Packing	42×25×24CM/24PCS/13.5kg				

Overall dimension(mm)

接线位置

- ☒ 端口 1,2 : 交流输入
- ☒ 端口 3 : 接地⊕
- ☒ 端口 4,5 : 直流输出-V
- ☒ 端口 6,7 : 直流输出+V

Terminal Pin No. Assignment

- ☒ Pin 1,2 : AC input
- ☒ Pin 3 : GND⊕
- ☒ Pin 4,5 : DC output-V
- ☒ Pin 6,7 : DC output+V

