

Summary

- > Single output: power 240W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

125.2x125.2x100mm

Specification	Model	DRP-240-24	DRP-240-48
DC output voltage, current		24V 0~10A	48V 0~5A
Wave and noise		80mVp-p	150mVp-p
Inlet wire stability		± 0.5%	± 0.5%
Load stability		± 1%	± 0.5%
Efficiency		84%	85%
Adjustable range for DC voltage		± 10%	± 10%
Input voltage range		85~264VAC 120~370VDC 47~63Hz	
Impact current		Cold start current 27A/115VAC 45A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		36~36V for 24V model; 54~60V for 48V model	
Setup, rise, hold up time		800ms, 40ms, 20ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10℃~+50℃	
Dimension		125.2×125.2×100mm	
Weight		1.2kg	
Packing		41.5×27.5×25CM/12PCS/14.5kg	

Overall dimension(mm)

