

Summary

- > Single output: power 200W
- > Input voltage: 180~264VAC 254~370VDC



General Specification

240x69x43mm

Specification	Model	LPV-200-12	LPV-200-24
DC output voltage, current		12V 0~16.5A	24V 0~8.3A
Wave and noise		150mVp-p	240mVp-p
Inlet wire stability		±0.5%	±0.5%
Load stability		±1%	±0.5%
Efficiency		81%	83%
Adjustable range for DC voltage		12V ±5%	24V ±5%
Input voltage range		180~264VAC 254~370VDC 47~63Hz	
Impact current		Cold start current 30A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		121%~142% shut down O/P voltage, re-power on to recover	
Setup, rise, hold up time		1000ms, 30ms, 24ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10℃~+50℃	
Dimension		240×69×43mm	
Weight		1.2kg	
Packing		47.5×28.5×18.5CM/18PCS/21.5kg	

Overall dimension(mm)

