

Summary

- > Single output: power 250W
- > Input voltage: 180~264VAC 254~370VDC



General Specification

233x122x60mm

Specification	Model	LPV-250-12	LPV-250-24
DC output voltage, current		12V 0~20A	24V 0~10A
Wave and noise		150mVp-p	240mVp-p
Inlet wire stability		± 0.5%	± 0.5%
Load stability		± 1%	± 0.5%
Efficiency		81%	83%
Adjustable range for DC voltage		12V ± 5%	24V ± 5%
Input voltage range		180~264VAC 254~370VDC 47~63Hz	
Impact current		Cold start current 30A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		121%~142% shut down O/P voltage, re-power on to recover	
Setup, rise, hold up time		1000ms, 30ms, 24ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10℃ ~+50℃	
Dimension		233×122×60mm	
Weight		2.5kg	
Packing		41×26×23CM/9PCS/22.5kg	

Overall dimension(mm)

