

Summary

- > Single output: power 30W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

222x30x20mm

Specification	Model	LPV-30-12	LPV-30-24
DC output voltage, current		12V 0~2.5A	24V 0~1.25A
Wave and noise		100mVp-p	100mVp-p
Inlet wire stability		±0.5%	±0.5%
Load stability		±1%	±0.5%
Efficiency		78%	80%
Adjustable range for DC voltage		12V ±5%	24V ±5%
Input voltage range		85~264VAC 120~370VDC 47~63Hz	
Impact current		Cold start current 30A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		121%~142% shut down O/P voltage, re-power on to recover	
Setup, rise, hold up time		100ms, 60ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10℃~+50℃	
Dimension		222×30×20mm	
Weight		0.25kg	
Packing		47×24×18.5CM/80PCS/20kg	

Overall dimension(mm)

