

Summary

- > Single output: power 60W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

190x47x38mm

Specification	Model	LPV-60-12	LPV-60-24
DC output voltage, current		12V 0~5A	24V 0~2.5A
Wave and noise		100mVp-p	150mVp-p
Inlet wire stability		±0.5%	±0.5%
Load stability		±1%	±0.5%
Efficiency		81%	83%
Adjustable range for DC voltage		12V ±5%	24V ±5%
Input voltage range		85~264VAC 120~370VDC 47~63Hz	
Impact current		Cold start current 30A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		121%~142% shut down O/P voltage, re-power on to recover	
Setup, rise, hold up time		500ms, 20ms, 24ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10℃~+50℃	
Dimension		190×47×38mm	
Weight		0.6kg	
Packing		44×20×19CM/24PCS/14.5kg	

Overall dimension(mm)

