

Summary

- > Single output: power 10W
- > Input voltage: 90~264VAC



General Specification

118×35×26mm

Specification	Model	LPV-10-5E	LPV-10-12E	LPV-10-15E	LPV-10-24E
DC output voltage, current		5V 0~2A	12V 0~0.8A	15V 0~0.6A	24V 0~0.4A
Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p
Inlet wire stability		± 1%	± 1%	± 1%	± 1%
Load stability		± 2%	± 2%	± 2%	± 2%
Efficiency		77%	81%	83%	83%
Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
Input voltage range	90~264VAC 127~370VDC 47~63Hz				
Impact current	COLD START 70A(twidth=215 s measured at 50% Ipeak) at 230VAC 0.55A/115VAC 0.35A/230VAC				
Overload protection	110%~150% cut off the output, automatic recovery				
Over voltage protection	Protection type : Shut off o/p voltage, clamping by zener diode				
Setup, rise, hold up time	500ms, 20ms, 16ms/230VAC at full load				
Withstand voltage	I/P-O/P: 3kVAC				
Isolation resistance	I/P-O/P: 500VDC / 100MΩ				
Working temperature	-20 C ~+50 C				
Dimension	118×35×26mm				
Weight	0.22kg				
Packing	60PCS/13.5kg				

Overall dimension(mm)