

Summary

- > Single output: power 20W
- > Input voltage: 90~264VAC



General Specification

118×35×26mm

Specification	Model	LPV-20-5E	LPV-20-12E	LPV-20-15E	LPV-20-24E
DC output voltage, current		5V 0~3A	12V 0~1.67A	15V 0~1.33A	24V 0~0.84A
Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p
Inlet wire stability		±1%	±1%	±1%	±1%
Load stability		±2%	±2%	±2%	±2%
Efficiency		77%	81%	83%	83%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		90~264VAC 127~370VDC 47~63Hz			
Impact current		COLD START 70A(twidth=215 s measured at 50% Ipeak) at 230VAC 0.55A/115VAC 0.35A/230VAC			
Overload protection		110%~150% cut off the output, automatic recovery			
Over voltage protection		Protection type : Shut off o/p voltage, clamping by zener diode			
Setup, rise, hold up time		500ms, 20ms, 16ms/230VAC at full load			
Withstand voltage		I/P-O/P: 3kVAC			
Isolation resistance		I/P-O/P: 500VDC / 100MΩ			
Working temperature		-20℃~+50℃			
Dimension		118×35×26mm			
Weight		0.22kg			
Packing		60PCS/13.5kg			

Overall dimension(mm)