

Summary

- > Single output: power 60W
- > Input voltage: 90~264VAC



General Specification

162.5×42.5×32mm

Specification	Model	LPV-60-5E	LPV-60-12E	LPV-60-15E	LPV-60-24E	LPV-60-36E
DC output voltage, current		5V 0~8A	12V 0~5A	15V 0~4A	24V 0~2.5A	36V 0~1.67A
Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p	150mVp-p
Inlet wire stability		± 1%	± 1%	± 1%	± 1%	± 1%
Load stability		± 6%	± 2%	± 2%	± 2%	± 2%
Efficiency		76%	83%	83%	86%	86%
Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%	± 10%
Input voltage range	90~264VAC 127~370VDC 47~63Hz					
Impact current	Cold start 60A (twidh =525μs measured at 50% Ipeak) at 230VAC 1.2A/115VAC 1A/230VAC					
Overload protection	110%~150% rated output power. Protection type : Hiccup mode, recovers automatically after fault condition is removed					
Over voltage protection	Protection type : Shut down O/P voltage, re-power on to recover					
Setup, rise, hold up time	500ms, 20ms, 16ms/230VAC at full load					
Withstand voltage	I/P-O/P: 3kVAC					
Isolation resistance	I/P-O/P: 500VDC / 100MΩ					
Working temperature	-20 C ~+50 C					
Dimension	462.5×42.5×32mm					
Weight	0.4kg					
Packing	30PCS/12kg					

Overall dimension(mm)