

### 概述 Summary

- > 单组输出: 功率10W  
Single output: power 10W
- > 输入电压: 85 ~ 264VAC 120 ~ 370VDC  
Input voltage: 85 ~ 264VAC 120 ~ 370VDC



### 常见规格 General Specification

22.5×90×100mm

性能 Specification	型号 Model	MDR-10-5	MDR-10-12	MDR-10-15	MDR-10-24
直流输出电压、电流 DC output voltage, current		5V 0~2A	12V 0~0.84A	15V 0~0.6A	24V 0~0.42A
纹波及噪音 Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p
进线稳定度 Inlet wire stability		±1%	±1%	±1%	±1%
负载稳定度 Load stability		±1%	±1%	±1%	±1%
效率 Efficiency		76%	80%	81%	84%
直流电压可调范围 Adjustable range for DC voltage		±2%	±1%	±1%	±1%
输入电压范围 Input voltage range	85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz				
冲击电流 Impact current	冷启动电流 Cold start current 20A/115VAC 40A/230VAC				
过载保护 Overload protection	105% ~ 160%切断输出, 自动恢复 105% ~ 160% cut off the output, automatic recovery				
过电压保护 Over voltage protection	120% ~ 140%关闭输出, 电源重启后可恢复输出 120% ~ 140% shut down O/P voltage, re-power on to recover				
启动、上升、保持时间 Setup, rise, hold up time	500ms, 30ms/230VAC满负载 at full load 1000ms, 30ms/115VAC 满负载 at full load				
耐压性 Withstand voltage	输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
隔离电阻 Isolation resistance	输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ				
工作温度 Working temperature	-10℃ ~ +50℃				
尺寸 Dimension	22.5×90×100mm				
重量 Weight	0.19kg				
包装 Packing	45.5×31.5×23CM/90PCS/18kg				

### 外形尺寸 Overall dimension(mm)

