

Summary

- > Single output: power 35W
- > Input voltage: 85~264VAC/120~370VDC



General Specification

84×58×38mm

Specification	Model	MS-35-5	MS-35-12	MS-35-15	MS-35-24
DC output voltage, current		5V 0~3A	12V 0~3A	15V 0~2.4A	24V 0~1.5A
Wave and noise		60mVp-p	80mVp-p	100mVp-p	100mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		77%	81%	83%	84%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	85~264VAC/120~370VDC 47~63Hz				
Impact current	Cold start current 30A/230VAC				
Overload protection	105%~150% cut off the output, automatic recovery				
Over voltage protection	115%~135% shut down O/P voltage, re-power on to recover				
Setup, rise, hold up time	300ms, 50ms, 80ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	84×58×38mm				
Weight	0.22kg				
Packing	38×35×24CM/100PCS/22kg				

Overall dimension(mm)

- ☐ 接线位置
- ☐ 端口 1,2 : 交流输入
 - ☐ 端口 3 : 接地⊕
 - ☐ 端口 4,5 : 直流输出-V
 - ☐ 端口 6,7 : 直流输出+V
- ☐ Terminal Pin No.Assignment
- ☐ Pin 1,2 : AC input
 - ☐ Pin 3 : GND⊕
 - ☐ Pin 4,5 : DC output-V
 - ☐ Pin 6,7 : DC output+V

