

Summary

- > Single output: power 60W
- > Input voltage: 85~264VAC/120~370VDC



General Specification

111×78×36mm

Specification	Model	MS-60-5	MS-60-12	MS-60-15	MS-60-24
DC output voltage, current		5V 0~12A	12V 0~5A	15V 0~4A	24V 0~2.5A
Wave and noise		75mVp-p	100mVp-p	100mVp-p	100mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		80%	82%	82%	84%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	85~264VAC/120~370VDC 47~63Hz				
Impact current	Cold start current 15A/115VAC 30A/230VAC				
Overload protection	105%~150% cut off the output, automatic recovery				
Other protection	Over current protection / Short-circuit protection				
Setup, rise, hold up time	200ms, 100ms, 20ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	111×78×36mm				
Weight	0.27kg				
Packing	42×35×25CM/80PCS/21kg				

Overall dimension(mm)

- ☒ 接线位置
- ☒ 端口 1,2: 交流输入
 - ☒ 端口 3: 接地
 - ☒ 端口 4: 直流输出-V
 - ☒ 端口 5: 直流输出+V
- ☒ Terminal Pin No.Assignment
- ☒ Pin 1,2: AC input
 - ☒ Pin 3: GND
 - ☒ Pin 4: DC output-V
 - ☒ Pin 5: DC output+V

