

Summary

- > Single output: power 10W
- > Input voltage: 85~264VAC/120~370VDC



General Specification

78×48×21mm

Specification	Model	MSF-10-5	MSF-10-12	MSF-10-15	MSF-10-24
DC output voltage, current		5V 0~2A	12V 0~1A	15V 0~0.8A	24V 0~0.5A
Wave and noise		50mVp-p	50mVp-p	50mVp-p	50mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		71%	73%	74%	75%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	85~264VAC/120~370VDC 47~63Hz				
Impact current	Cold start current 30A/230VAC				
Overload protection	105%~135% cut off the output, automatic recovery				
Other protection	Over current protection / Short-circuit protection				
Setup, rise, hold up time	200ms, 50ms, 20ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	78×48×21mm				
Weight	0.15kg				
Packing	24.5×17.5×26.5CM/100PCS/15kg				

Overall dimension(mm)

