

Summary

- > Single output: power 20W
- > Input voltage: 85~264VAC/120~370VDC



General Specification

97×58×25mm

Specification	Model	MSF-20-5	MSF-20-12	MSF-20-15	MSF-20-24
DC output voltage, current		5V 0~4A	12V 0~2A	15V 0~1.6A	24V 0~1A
Wave and noise		50mVp-p	50mVp-p	50mVp-p	50mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		72%	74%	74%	76%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		85~264VAC/120~370VDC 47~63Hz			
Impact current		Cold start current 30A/230VAC			
Overload protection		105%~135% cut off the output, automatic recovery			
Other protection		Over current protection / Short-circuit protection			
Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature		-10℃~+50℃			
Dimension		97×58×25mm			
Weight		0.19kg			
Packing		28.5×21.6×32CM/100PCS/19kg			

Overall dimension(mm)

