

Summary

- > Single output: power 240W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

63x125.2x113.5mm

Specification	Model	NDR-240-24	NDR-240-48
DC output voltage, current		24V 0~10A	48V 0~5A
Wave and noise		150mVp-p	150mVp-p
Inlet wire stability		± 0.5%	± 0.5%
Load stability		± 1%	± 0.5%
Efficiency		88%	85%
Adjustable range for DC voltage		± 10%	± 10%
Input voltage range		85~264VAC 120~370VDC 47~63Hz	
Impact current		Cold start current 30A/115VAC 60A/230VAC	
Overload protection		105%~150% cut off the output, automatic recovery	
Over voltage protection		120%~140% shut down O/P voltage, re-power on to recover	
Setup, rise, hold up time		1500ms, 100ms/230VAC at full load	
Withstand voltage		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute	
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
Working temperature		-10 C ~+50 C	
Dimension		63×125.2×113.5mm	
Weight		1.2kg	
Packing		41.5×27.5×26CM/12PCS/15kg	

Overall dimension(mm)

