

Summary

- > Single output: power 120W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

199×98×38mm

Specification	Model	S-120-12	S-120-15	S-120-24	S-120-48
DC output voltage, current		12V 0~10A	15V 0~8A	24V 0~5A	48V 0~2.5A
Wave and noise		100mVp-p	100mVp-p	100mVp-p	100mVp-p
Inlet wire stability		±0.3%	±0.3%	±0.2%	±0.2%
Load stability		±0.3%	±0.3%	±0.2%	±0.2%
Efficiency		81%	82%	84%	84%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz			
Impact current		Cold start current 30A/115VAC 60A/230VAC			
Overload protection		105%~150% cut off the output, automatic recovery			
Over voltage protection		110%~135% shut down O/P voltage, re-power on to recover			
Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature		-10℃~+50℃			
Dimension		199×98×38mm			
Weight		0.6kg			
Packing		43×32.5×24CM/30PCS/18kg			

Overall dimension(mm)

接线位置

- 端口 1,2 : 交流输入
- 端口 3 : 接地
- 端口 4,5 : 直流输出-V
- 端口 6,7 : 直流输出+V

Terminal Pin No.Assignment

- Pin 1,2 : AC input
- Pin 3 : GND
- Pin 4,5 : DC output-V
- Pin 6,7 : DC output+V

