

Summary

- > Single output: power 1500W
- > Input voltage: 100~132VAC/200~264VAC by switch



General Specification

291×132×68mm

Specification	Model	S-1500-12	S-1500-24	S-1500-36	S-1500-48
DC output voltage, current		12V 0~125A	24V 0~62.5A	36V 0~41A	48V 0~32A
Wave and noise		150mVp-p	180mVp-p	180mVp-p	240mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		80%	81%	83%	84%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		100~132VAC/200~264VAC by switch 254~370VDC 47~63Hz			
Impact current		Cold start current 45A/230VAC			
Overload protection		105%~135% cut off the output, automatic recovery			
Other protection		Over current protection / Short-circuit protection			
Setup, rise, hold up time		2000ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature		-10℃~+50℃			
Dimension		291×132×68mm			
Weight		2.65kg			
Packing		37.5×31×25.5CM/6PCS/16kg			

Overall dimension(mm)

