

Summary

- > Single output: power 200W
- > Input voltage: 90~132VAC or 180~264VAC



General Specification

199×110×50mm

Specification	Model	S-200-5	S-200-12	S-200-24	S-200-48
DC output voltage, current		5V 0~40A	12V 0~16.5A	24V 0~8.5A	48V 0~4.2A
Wave and noise		150mVp-p	150mVp-p	180mVp-p	200mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		79%	82%	83%	86%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	90~132VAC or 180~264VAC 47~63Hz				
Impact current	Cold start current 15A/115VAC 30A/230VAC				
Overload protection	105%~201% cut off the output, automatic recovery				
Other protection	Over current protection / Short-circuit protection				
Setup, rise, hold up time	200ms, 50ms, 20ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	199×110×50mm				
Weight	0.9kg				
Packing	42×31.5×26CM/20PCS/18kg				

Overall dimension(mm)

接线位置

- 端口 1,2 : 交流输入
- 端口 3 : 接地
- 端口 4,5,6 : 直流输出-V
- 端口 7,8,9 : 直流输出+V

Terminal Pin No. Assignment

- Pin 1,2 : AC input
- Pin 3 : GND
- Pin 4,5,6 : DC output-V
- Pin 7,8,9 : DC output+V

