

### Summary

- > Single output: power 2000W
- > Input voltage: 200~264VAC



### General Specification

291×132×136mm

| Specification                   | Model | S-2000-24                                               | S-2000-36 | S-2000-48 | S-2000-60 |
|---------------------------------|-------|---------------------------------------------------------|-----------|-----------|-----------|
| DC output voltage, current      |       | 24V 0~83A                                               | 36V 0~55A | 48V 0~41A | 60V 0~33A |
| Wave and noise                  |       | 120mVp-p                                                | 200mVp-p  | 240mVp-p  | 480mVp-p  |
| Inlet wire stability            |       | ±0.5%                                                   | ±0.5%     | ±0.5%     | ±0.5%     |
| Load stability                  |       | ±0.5%                                                   | ±0.5%     | ±0.5%     | ±0.5%     |
| Efficiency                      |       | 80%                                                     | 86%       | 87%       | 88%       |
| Adjustable range for DC voltage |       | ±10%                                                    | ±10%      | ±10%      | ±10%      |
| Input voltage range             |       | 200~264VAC 47~63Hz                                      |           |           |           |
| Impact current                  |       | Cold start current 45A/230VAC                           |           |           |           |
| Overload protection             |       | 105%~135% cut off the output, automatic recovery        |           |           |           |
| Over voltage protection         |       | 115%~150% shut down O/P voltage, re-power on to recover |           |           |           |
| Setup, rise, hold up time       |       | 2000ms, 50ms, 20ms/230VAC at full load                  |           |           |           |
| Withstand voltage               |       | I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute       |           |           |           |
| Isolation resistance            |       | I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ                   |           |           |           |
| Working temperature             |       | -10℃~+50℃                                               |           |           |           |
| Dimension                       |       | 291×132×136mm                                           |           |           |           |
| Weight                          |       | 5.3kg                                                   |           |           |           |
| Packing                         |       | 38×37.5×21CM/2PCS/11kg                                  |           |           |           |

### Overall dimension(mm)

