

Summary

- > Single output: power 25W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

98×97×35mm

Specification	Model	S-25-5	S-25-12	S-25-15	S-25-24
DC output voltage, current		5V 0~5A	12V 0~2.1A	15V 0~1.67A	24V 0~1.1A
Wave and noise		50mVp-p	50mVp-p	75mVp-p	100mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		65%	68%	70%	72%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz				
Impact current	Cold start current 15A/115VAC 30A/230VAC				
Overload protection	105%~150% cut off the output, automatic recovery				
Other protection	Over current protection / Short-circuit protection				
Setup, rise, hold up time	200ms, 100ms, 30ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	98×97×35mm				
Weight	0.3kg				
Packing	43×32.5×24CM/60PCS/18kg				

Overall dimension(mm)

- ☒ 接线位置
- ☒ 端口 1: 直流输出+V
- ☒ 端口 2: 直流输出-V
- ☒ 端口 3: 接地⊕
- ☒ 端口 4,5: 交流输入
- ☒ Terminal Pin No.Assignment
- ☒ Pin 1: DC output+V
- ☒ Pin 2: DC output-V
- ☒ Pin 3: GND⊕
- ☒ Pin 4,5: AC input

