

Summary

- > Single output: power 3000W
- > Input voltage: 200~264VAC



General Specification

291×132×136mm

Specification	Model	S-3000-24	S-3000-36	S-3000-48	S-3000-60
DC output voltage, current		24V 0~125A	36V 0~83A	48V 0~62.5A	60V 0~50A
Wave and noise		120mVp-p	200mVp-p	240mVp-p	480mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		80%	86%	87%	88%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		200~264VAC 47~63Hz			
Impact current		Cold start current 120A/230VAC			
Overload protection		105%~135% cut off the output, automatic recovery			
Over voltage protection		115%~150% shut down O/P voltage, re-power on to recover			
Setup, rise, hold up time		2000ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature		-10℃~+50℃			
Dimension		291×132×136mm			
Weight		5.3kg			
Packing		38×37.5×21CM/2PCS/11kg			

Overall dimension(mm)

