

S-350W Single output power supply

Summary

- > Single output: power 350W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

215×115×50mm

Specification \ Model	S-350-5	S-350-12	S-350-24	S-350-48
DC output voltage, current	5V 0~50A	12V 0~29A	24V 0~14.6A	48V 0~7.3A
Wave and noise	150mVp-p	150mVp-p	150mVp-p	200mVp-p
Inlet wire stability	±0.5%	±0.5%	±0.5%	±0.5%
Load stability	±0.5%	±0.5%	±0.5%	±0.5%
Efficiency	73%	83%	85%	86%
Adjustable range for DC voltage	±10%	±10%	±10%	±10%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz			
Impact current	Cold start current 25A/115VAC 50A/230VAC			
Overload protection	105%~135% cut off the output, automatic recovery			
Over voltage protection	115%~150% shut down O/P voltage, re-power on to recover			
Setup, rise, hold up time	200ms, 50ms, 20ms/230VAC at full load			
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature	-10℃ ~+50℃			
Dimension	215×115×50mm			
Weight	1kg			
Packing	45.5×31.5×26CM/20PCS/20kg			

Overall dimension(mm)

