

Summary

- > Single output: power 400W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

215×115×50mm

Specification	Model	S-400-5	S-400-12	S-400-24	S-400-48
DC output voltage, current		5V 0~60A	12V 0~33A	24V 0~16.5A	48V 0~8.3A
Wave and noise		100mVp-p	150mVp-p	150mVp-p	200mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		73%	82%	83%	85%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz				
Impact current	Cold start current 25A/115VAC 50A/230VAC				
Overload protection	105%~135% cut off the output, automatic recovery				
Over voltage protection	115%~150% shut down O/P voltage, re-power on to recover				
Setup, rise, hold up time	200ms, 50ms, 20ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	215×115×50mm				
Weight	1.1kg				
Packing	45.5×31.5×26CM/20PCS/22kg				

Overall dimension(mm)

