

Summary

- > Single output: power 75W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

159×98×38mm

Specification	Model	S-75-12	S-75-15	S-75-24	S-75-48
DC output voltage, current		12V 0~6A	15V 0~5A	24V 0~3.2A	48V 0~1.5A
Wave and noise		100mVp-p	100mVp-p	120mVp-p	150mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		78%	79%	82%	83%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz			
Impact current		Cold start current 15A/115VAC 30A/230VAC			
Overload protection		105%~150% cut off the output, automatic recovery			
Other protection		Over current protection / Short-circuit protection			
Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature		-10℃~+50℃			
Dimension		159×98×38mm			
Weight		0.55kg			
Packing		34×32×24CM/30PCS/16.5kg			

Overall dimension(mm)

