

Summary

- > Single output: power 30W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

129×98×38mm

Specification	T-30A			T-30B			T-30C			T-30D		
	CH1	CH2	CH3	CH1	CH2	CH3	CH1	CH2	CH3	CH1	CH2	CH3
DC output voltage, current	5V 0~3A	12V 0~1A	-5V 0~0.5A	5V 0~3A	12V 0~1A	-12V 0~0.5A	5V 0.5~3A	15V 0.1~0.5A	-15V 0.1~0.5A	5V 0.5~3A	12V 0.1~1.5A	24V 0.1~1.5A
Wave and noise	50mVp-p	100mVp-p	50mVp-p	50mVp-p	100mVp-p	100mVp-p	50mVp-p	100mVp-p	100mVp-p	50mVp-p	100mVp-p	120mVp-p
Inlet wire stability	±0.5%	±1%	±1%	±0.5%	±1%	±1%	±0.5%	±1%	±1%	±0.5%	±1%	±1%
Load stability	±0.5%	±5%	±5%	±0.5%	±5%	±5%	±1%	±4%	±4%	±1%	±4%	±4%
Efficiency	70%			72%			72%			72%		
Adjustable range for DC voltage	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz											
Impact current	Cold start current 18A/115VAC 36A/230VAC											
Overload protection	105%~150% cut off the output, automatic recovery											
Over voltage protection	CH1:115%~135% shut down O/P voltage, re-power on to recover											
Setup, rise, hold up time	200ms, 100ms, 30ms/230VAC at full load											
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute											
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ											
Working temperature	-10 C ~+50 C											
Dimension	129×98×38mm											
Weight	0.4kg											
Packing	43×32.5×24CM/45PCS/18kg											

Overall dimension(mm)

