

T-60W Triple output power supply

Summary

- > Single output: power 60W
- > Input voltage: 85~264VAC 120~370VDC



General Specification

159×98×38mm

Model Specification	T-60A			T-60B			T-60C			T-60D		
	CH1	CH2	CH3	CH1	CH2	CH3	CH1	CH2	CH3	CH1	CH2	CH3
DC output voltage, current	5V 0~5A	12V 0~2.5A	-5V 0~0.5A	5V 0~5A	12V 0~2.5A	-12V 0~0.5A	5V 0~5A	15V 0~2A	-15V 0~0.5A	5V 0.5~5A	12V 0.2~2.5A	24V 0.2~0.5A
Wave and noise	50mVp-p	100mVp-p	100mVp-p	100mVp-p	120mVp-p	120mVp-p	100mVp-p	120mVp-p	120mVp-p	80mVp-p	100mVp-p	100mVp-p
Inlet wire stability	±0.5%	±1%	±0.5%	±0.5%	±1%	±0.5%	±0.5%	±1%	±0.5%	±0.5%	±1%	±1%
Load stability	±1%	±4%	±1%	±1%	±4%	±4%	±4%	±4%	±1%	±1%	±4%	±1%
Efficiency	72%			72%			72%			72%		
Adjustable range for DC voltage	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%
Input voltage range	85~264VAC 120~370VDC 47~63Hz											
Impact current	Cold start current 30A/115VAC 60A/230VAC											
Overload protection	105%~150% cut off the output, automatic recovery											
Over voltage protection	CH1:115%~135% shut down O/P voltage, re-power on to recover											
Setup, rise, hold up time	300ms, 50ms, 80ms/230VAC at full load											
Withstand voltage	I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV 1minute											
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ											
Working temperature	-10℃~+50℃											
Dimension	159×98×38mm											
Weight	0.55kg											
Packing	34×32×24CM/30PCS/16.5kg											

Overall dimension(mm)

