

Summary

- > Single output: power 35W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

129×98×38mm

Specification	Model	S-35-5	S-35-12	S-35-15	S-35-24
DC output voltage, current		5V 0~7A	12V 0~3A	15V 0~2.4A	24V 0~1.5A
Wave and noise		70mVp-p	70mVp-p	100mVp-p	100mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±1%	±0.5%	±0.5%	±0.5%
Efficiency		70%	76%	78%	78%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz				
Impact current	Cold start current 18A/115VAC 36A/230VAC				
Overload protection	105%~150% cut off the output, automatic recovery				
Other protection	Over current protection / Short-circuit protection				
Setup, rise, hold up time	200ms, 100ms, 30ms/230VAC at full load				
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ				
Working temperature	-10℃~+50℃				
Dimension	129×98×38mm				
Weight	0.4kg				
Packing	43×32.5×24CM/45PCS/18kg				

Overall dimension(mm)

- 接线位置
- 端口 1,2: 交流输入
 - 端口 3: 接地
 - 端口 4: 直流输出-V
 - 端口 5: 直流输出+V
- Terminal Pin No.Assignment
- Pin 1,2 : AC input
 - Pin 3 : GND
 - Pin 4 : DC output-V
 - Pin 5 : DC output+V

