

Summary

- > Single output: power 600W
- > Input voltage: 90~132VAC/180~264VAC by switch



General Specification

238×124×65mm

Specification \ Model	S-600-15	S-600-24	S-600-36	S-600-48
DC output voltage, current	15V 0~40A	24V 0~25A	36V 0~16.7A	48V 0~12.5A
Wave and noise	100mVp-p	150mVp-p	150mVp-p	150mVp-p
Inlet wire stability	±0.5%	±0.5%	±0.5%	±0.5%
Load stability	±0.5%	±0.5%	±0.5%	±0.5%
Efficiency	83%	85%	86%	87%
Adjustable range for DC voltage	±10%	±10%	±10%	±10%
Input voltage range	90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz			
Impact current	Cold start current 25A/115VAC 50A/230VAC			
Overload protection	105%~300% cut off the output, automatic recovery			
Over voltage protection	115%~140% shut down O/P voltage, re-power on to recover			
Setup, rise, hold up time	800ms, 20ms, 36ms/230VAC at full load			
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC / 100MΩ			
Working temperature	-10℃ ~ +50℃			
Dimension	238×124×65mm			
Weight	1.5kg			
Packing	44×26×27CM/12PCS/18kg			

Overall dimension(mm)

接线位置

- 端口 1,2 : 交流输入
- 端口 3 : 接地⊕
- 端口 4,5,6 : 直流输出-V
- 端口 7,8,9 : 直流输出+V

Terminal Pin No.Assignment

- Pin 1,2 : AC input
- Pin 3 : GND⊕
- Pin 4,5,6 : DC output-V
- Pin 7,8,9 : DC output+V

