

Summary

- > Single output: power 150W
- > Input voltage: 180~264VAC/235~373VDC



General Specification

190×49×34mm

Specification	Model	XLG-150-12	XLG-150-24	XLG-150-36	XLG-150-48
DC output voltage, rated current		12V 12.5A	24V 6.3A	36V 4.2A	48V 3.2A
Wave and noise		150mVp-p	180mVp-p	180mVp-p	200mVp-p
Line regulation		± 0.5%	± 0.5%	± 0.5%	± 0.5%
Load regulation		± 2%	± 0.5%	± 0.5%	± 0.5%
Efficiency		90%	91%	92%	93%
Voltage accuracy		± 3%	± 2%	± 2%	± 2%
Input voltage range		180~264VAC/253~373VDC 47~63Hz			
Impact current		Cold start current 45A/230VAC			
Overcurrent protection		95%~108% of the rated output current starts overcurrent limit, recover automatically after abnormal conditions are removed			
Short circuit protection		Hiccup mode: recover automatically normal output after abnormal conditions are removed			
Setup, rise, hold up time		500ms, 80ms, 16ms/230VAC (at full load)			
Pressure resistance		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 100M Ohms / 500VDC / 25 C / 70%RH			
Working temperature		-20 C ~ +60 C			
Dimension		190×49×34mm			
Weight		0.65kg			
Packing		30PCS/20.5kg/0.025 cubic meters			

Overall dimension(mm)

单位:mm

