



XLG-800W Single output waterproof power supply

Summary

- > Single output: power 800W
- > Input voltage: 180~264VAC/245~373VDC

General Specification

265×120×56mm

Specification	Model	XLG-800-24	XLG-800-36	XLG-800-48	XLG-800-60
DC output voltage, rated current		24V 27A	36V 22A	48V 16.5A	60V 13.5A
Wave and noise		200mVp-p	220mVp-p	240mVp-p	240mVp-p
Line regulation		±0.5%	±0.5%	±0.5%	±0.5%
Load regulation		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		92.5%	93%	93.5%	94%
Voltage accuracy		±2%	±1.5%	±1.5%	±1.5%
Input voltage range		180~264VAC/245~373VDC 47~63Hz			
Impact current		Cold start current 65A/230VAC			
Overcurrent protection		95%~108% of the rated output current starts overcurrent limit, recover automatically after abnormal conditions are removed			
Short circuit protection		Hiccup mode: recover automatically normal output after abnormal conditions are removed			
Setup, rise, hold up time		500ms, 50ms, 24ms/230VAC (at full load)			
Pressure resistance		I/P-O/P: 1.5kV I/P-FG:1.5kV O/P-FG: 0.5kV			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 100M Ohms / 500VDC / 25 C /70%RH			
Working temperature		-20 C ~ +60 C			
Dimension		265×120×56mm			
Weight		2.75kg			
Packing		6PCS/17.5kg/0.033 cubic meters			

Overall dimension(mm)

单位:mm

