

Summary

- > Single output: power 150W
- > Input voltage: 95~264VAC/135~373VDC
- > PF>0.96/230VAC(at full load)



General Specification

190×49×34mm

Specification	Model	HLG-150-12	HLG-150-24	HLG-150-36	HLG-150-48
DC output voltage, rated current		12V 12.5A	24V 6.3A	36V 4.2A	48V 3.2A
Wave and noise		150mVp-p	151.2mVp-p	220mVp-p	220mVp-p
Line regulation		±0.5%	±0.5%	±0.5%	±0.5%
Load regulation		±2%	±0.5%	±0.5%	±0.5%
Efficiency		88%	90%	90.5%	91.5%
Voltage accuracy		±3%	±2%	±2%	±2%
Input voltage range		95~264VAC/135~373VDC 47~63Hz			
Impact current		Cold start current 45A/230VAC			
Overcurrent protection		95%~108% of the rated output current starts overcurrent limit, recover automatically after abnormal conditions are removed			
Short circuit protection		Hiccup mode: recover automatically normal output after abnormal conditions are removed			
Setup, rise, hold up time		500ms, 30ms, 20ms/230VAC (at full load)			
Pressure resistance		I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 100M Ohms / 500VDC / 25 C / 70%RH			
Working temperature		-20 C ~ +60 C			
Dimension		170×69×43mm			
Weight		0.75kg			
Packing		20PCS			

Overall dimension(mm)

