



HDR-150W单组输出导轨电源

HDR-150W Single output DIN rail power supply

概述 Summary

- > 单组输出: 功率150W
Single output: power 150W
- > 输入电压: 85~264V交流/120~370V直流
Input voltage: 85~264VAC/120~370VDC



常见规格 General Specification

105×90×54.5mm

性能 Specification		型号 Model	HDR-150-12	HDR-150-15	HDR-150-24	HDR-150-48
直流输出电压、电流 DC output voltage, current	115VAC		12V 0~10.2A	15V 0~8.55A	24V 0~5.31A	48V 0~2.72A
	230VAC		12V 0~11.3A	15V 0~9.5A	24V 0~6.25A	48V 0~3.2A
纹波及噪音 Wave and noise			100mVp-p	120mVp-p	150mVp-p	200mVp-p
进线稳定度 Inlet wire stability			±1%	±1%	±1%	±1%
负载稳定度 Load stability			±1%	±1%	±1%	±1%
效率 Efficiency			87%	88%	89%	89%
直流电压可调范围 Adjustable range for DC voltage			±10%	±10%	±10%	±10%
输入电压范围 Input voltage range			85~264V交流/120~370V直流 47~63Hz 85~264VAC/120~370VDC 47~63Hz			
冲击电流 Impact current			冷启动电流 35A/115VAC 70A/230VAC Cold start current			
过载保护 Overload protection			105%~150%切断输出, 自动恢复 105%~150%cut off the output, automatic recovery			
过电压保护 Overvoltage protection			115%~140%额定输出功率 保护类型: 打嗝模式, 故障排除后自动回复 115%~140% rated output power Protection type: Hiccup mode, recovers automatically after fault condition is removed			
启动、上升、保持时间 Setup, rise, hold up time			1500ms, 80ms/230VAC 1500ms, 80ms/115VAC(满载时)			
耐压性 Withstand voltage			输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance			输入输出间 输入与外壳间 输出与外壳间: 500VDC/100M I/P-O/P I/P-FG O/P-FG: 100M Ohms / 500VDC / 25 °C / 70%RH			
工作温度 Working temperature			-20 °C ~ +70 °C			
尺寸 Dimension			105 × 90 × 54.5mm			
重量 Weight			0.3kg			
包装 Packing			/			

外形尺寸 Overall dimension(mm)

接线位置


- 端子 1,2: 交流输入
- 端子 3,4: 直流输出 -V
- 端子 5,6: 直流输出+V

Terminal Pin No.Assignment

- Pin 1,2: AC input
- Pin 3,4: DC output -V
- Pin 5,6: DC output+V

端子Pin脚定义

Pin脚编号	Pin脚功能	Pin脚编号	Pin脚功能
1	AC/N	3,4	-V
2	AC/L	5,6	+V



ADMISSIBLE DIN-RAIL: TS35/7.5 OR TS35/15

